

Grade	OD Size (inches)	No. of PCS	Length (inches)	Weight per PC
15-5 A	8	1	4.875	
15-5 A	12	1	3.5	
17-4 A	0.5	1	100.75	
17-4 A	0.625	1	41.125	
17-4 A	2.25	6	16	18
17-4 A	2.25	1	46.875	
17-4 A	6	1	2.625	
17-4 A	6	1	4.5	
17-4 A	6	1	7.75	
17-4 A	7.5	1	5	
17-4 H1025	1	3	7.25	2
17-4 H1025	1	3	10.25	3
17-4 H1025	1	1	70.25	
17-4 H1025	1.75	1	3.5	
17-4 H1025	1.75	1	9.75	
17-4 H1025	3.5	1	9.625	
17-4 H1025	3.75	1	8.125	
17-4 H1025	3.75	1	6.5	
17-4 H1025	3.75	1	11.125	
17-4 H1025	4	1	6.375	
17-4 H1025	7	1	3.375	
17-4 H1150	0.75	1	17.625	
17-4 H1150	6.25	1	7.25	
17-4 H1150	2.25	1	13.25	
17-4 H1150D	1.25	1	14.25	
17-4 H1150D	1.75	1	4	
17-4 H1150D	2.5	2	3.125	4
17-4 H1150D	3.5	1	3	
17-4 H1150D	3.5	3	3.375	9
17-4 H1150D	3.5	1	3.625	
17-4 H1150D	3.5	1	5.25	
17-4 H1150D	3.5	1	5.5	
17-4 H1150D	3.5	4	5.75	16
17-4 H1150D	3.5	3	5.375	15
17-4 H1150D	3.5	1	6.125	
17-4 H1150D	3.965	3	7.5	27
17-4 H1150D	3.965	1	6.125	
17-4 H1150D	4	1	7.875	
17-4 H1150D	4.5	1	6.75	
17-4 H1150D	4.75	1	4	
17-4 H1150D	5.25	1	5.5	
17-4 H1150D	5.5	1	4.75	
17-4 H1150D	5.5	4	5.625	40
17-4 H1150D	10.5	1	2	
316/316L	1.25	1	9.625	
316/316L	1.875	1	5.75	

316/316L	2	8	12.875-13.5	12
316/316L	2	1	42.5	
316/316L	3.375	1	8.125	
316/316L	3.375	1	8.375	
316/316L	3.375	1	12	
316/316L	1.375 HEX	1	30.75	
316/316L	1.375 HEX	1	52.5	
316/316L	1.5 HEX	1	7.75	
416 A	3	1	16.125	
6061 T6	13.5	1	8.375	
718 AMS 5662	2.25	1	5.375	
718 AMS 5662	3.75	1	8.875	
718 AMS 5663	0.25	1	27.875	
718 AMS 5663	2	1	3.5	
718 AMS 5663	2	1	4.125	
718 AMS 5663	2	1	5	
718 AMS 5663	2.25	1	3	
718 AMS 5663	2.25	1	5	
718 API NACE	0.75	1	4.75	
718 API NACE	1.125	1	15.25	
718 API NACE	1.375	1	20	
718 API NACE	1.375	1	6.25	
718 API NACE	10	2	2	55
718 HT	4	1	9.625	
725 API	1.5	5	10.375" -14"	7
ALLOY 500	1.75	1	12.125	
ALLOY 500	6	1	4.5	
ALLOY 625	1	1	23.875	
ALLOY 800	2.75	1	4.875	
MP35N NACE	1.5	1	1.25	
UNS 32750	1.5	1	33.5	
UNS 32750	1.5	1	38	
UNS 32750	3.75	1	8.25	
UNS S21800	1	1	109.625	
UNS S21800	2	1	8.25	
UNS S21800	2	1	18.125	
UNS S21800	2.5	1	7.5	
UNS S21800	2.5	1	8.5	
UNS S21800	3	1	10.375	
UNS S21800	3	1	4.5	
UNS S21800	2	1	24.25	
UNS S21800	2.5	1	6.875	
UNS S31803	2	1	3.875	
UNS S31803	4	1	4.75	
UNS S31803	5.5	1	6.75	
UNS S31803	9	1	3.125	
UNS S32750	4.5	1	7.25	

XM-19 Annealed	3	1	9.375	
XM-19 Annealed	4.75	1	4.125	
XM-19 Annealed	10.5	1	2.5	
XM-19 HS	1.25	1	10.5	
XM-19 HS	1.25	1	16.375	
XM-19 HS	1.5	1	5	
XM-19 HS	1.5	1	6.5	
XM-19 HS	1.5	1	21.25	
XM-19 HS	1.75	1	27.75	
XM-19 HS	1.875	1	3.375	
XM-19 HS	1.875	1	3.625	
XM-19 HS	1.875	1	9.625	
XM-19 HS	1.875	7	4-4.75	4
XM-19 HS	1.875	2	6.5	5
XM-19 HS	1.875	4	8.125-9	7
XM-19 HS	2	1	12.125	
XM-19 HS	2	1	13.5	
XM-19 HS	2	1	13.875	
XM-19 HS	5	1	7.5	
XM-19 HS	5	1	4.75	
XM-19 HS	1.5	1	14	
XM-19 HS	1.875	4	7.125-7.75	6
XM-19 HS	1.875	7	10.375-10.875	9
XM-19 HS	1.875	7	11-11.75	9
XM-19 HS	1.875	3	12.5-12.75	10

Total Weight
75
115
6
3
108
53
21
37
62
66
6
9
15
2
7
26
26
21
36
23
39
2
64
15
5
4
8
8
27
10
14
15
64
45
17
81
22
28
30
20
34
33
160
36
3
5

96
30
21
22
31
14
25
5
33
123
7
29
1
3
4
5
4
6
1
5
9
3
110
36
34
9
39
5
8
1
17
19
26
28
7
16
10
12
21
9
21
9
4
18
46
58
34

19
22
65
4
6
3
3
11
19
3
3
8
23
5
26
11
12
12
42
27
7
24
62
63
30